

THERMEX Vision V		Vision V 30	Vision V 50	Vision V 80	Vision V 100
Zapremina	lit	30	50	80	100
Volumen skladištenja	lit	30,06	50,85	80,50	100,10
Profil opterećenja		S	L	L	L
Energetski razred		B	C	C	C
Energetska efikasnost	%	35,2	38,5	38,3	38,4
Snaga	kW	1,5	1,5	1,5	1,5
Dnevna električna potrošnja	kWh	2,472	12,245	12,327	12,286
Godišnja električna potrošnja	kWh	524,1	2659,2	2666,2	2666,2
Radni napon	V/Hz	230/50	230/50	230/50	230/50
Min-Max. pritisak	Mpa	0,05 - 0,75	0,05 - 0,75	0,05 - 0,75	0,05 - 0,75
Vreme zagrevavanja $\Delta T = 45^{\circ}\text{C}$	Min	63	105	168	210
Količina mešane vode 45°C-on	lit	-	-	-	-
Fabričko podešen termostat	$^{\circ}\text{C}$	65 ± 3	65 ± 3	65 ± 3	65 ± 3
Max. podešena temperatura sa termostatom	$^{\circ}\text{C}$	75	75	75	75
Prikljucci					
Izlazna topla voda	inch	G 1/2"	G 1/2"	G 1/2"	G 1/2"
Ulazna hladna voda	inch	G 1/2"	G 1/2"	G 1/2"	G 1/2"
Mere					
Širina (X)	mm	340	380	450	450
Dubina (Y)	mm	340	380	450	450
Visina (Z)	mm	618	735	808	963
Magnezium anod	mm	$\varnothing 20 \times 300$	$\varnothing 20 \times 300$	$\varnothing 20 \times 300$	$\varnothing 20 \times 300$
Masa	kg	12	16	22	26
Zaštita od dodira		IPX4	IPX4	IPX4	IPX4
Nivo zvuka	dB	15	15	15	15

